

SOLAR CYCLE

SUN-KING

Batteries For Remote Power Systems

Amp Hour Capacity At 30°C

PART NO.	C100 TO 1.80 VPC	C20 TO 1.85 VPC	C10 TO 1.80 VPC	C5 TO 1.70 VPC	Internal Resistance Ω	Short Circuit Current Amps
HLH15	930	590	565	525	0.000387	5156.76
HLH17	1100	680	645	600	0.000353	5676.46
HLH19D	1200	770	710	675	0.000355	5705.79
HLH25D	1600	1034	967	900	0.000235	8479.4

D = DOUBLE POST CELLS

**** All Cells Have Heavy Duty Flexible Cables ****

Individual Cell Sizes

PART NO.	WEIGHT kg's +/- 5%	CELL LENGTH MM	CELL WIDTH MM	CELL HEIGHT MM	TOTAL CELL HEIGHT	PRICE EX GST
HLH15	29.8	125	158	510	535	
HLH17	33.6	141	158	510	535	
HLH19D	38.4	157	158	510	535	
HLH25D	44.9	205	158	510	535	

D = DOUBLE POST CELLS

Australian sales: Australian Windsun Power Pty Ltd. Ph: 0411 424 274. Email awsp@mail.com. Web: australianwindsunpower.com.au